



Technical Data Sheet for XLT2423

Single-Stage Thermoelectric Module



NOMINAL PERFORMANCE IN NITROGEN

Hot Side Temperature (°C)	27	50
ΔT_{max} (°C):	58	66
Q _{max} (watts):	95	106
I _{max} (amps):	19.0	18.8
V _{max} (vdc):	7.7	8.5
AC Resistance (ohms):	0.34	---

PRODUCT FEATURES

- RoHS EU Compliant
- Rated operating temperature of 125°C.
- Ceramic Material: Aluminum Oxide
- Designed for temperature cycling applications.
- Capable of rapid heating and cooling rates.
- Porch configuration for high strength leadwire connection.
- Superior nickel diffusion barriers on elements.
- High strength for rugged environment.
- RTV sealing option available.
- Lapped for multiple module applications.
- Diced option for further mechanical stress relief.
- Set of modules ACR matched available.

ORDERING OPTIONS

Model Number	Description
XLT2423-31AC	Undiced
XLT2423-34AC	Undiced, ACR matched set of 4
XLT2423-38AC	Undiced, ACR matched set of 8
XLT2423-41AC	Diced
XLT2423-42AC	Diced, ARC matched set of 2
XLT2423-44AC	Diced, ACR matched set of 4
XLT2423-48AC	Diced, ACR matched set of 8
XLT2423-51AC	Undiced, 10 inches long leadwires
XLT2423-61AC	Undiced, plastic tray packaging
XLT2423-71AC	Undiced, no leadwires
XLT2423-78AC	Undiced, ACR matched set of 8, no leadwires
XLT2423-81AC	Diced, no leadwires
XLT2423-88AC	Diced, ACR matched set of 8, no leadwires
XLT2423-98AC	Diced, ACR matched set of 8, 2.12 inches long leadwires

OPERATION CAUTIONS

For maximum reliability, storage and operation below 125°C in a non-condensing environment is recommended. To minimize thermal stress, use linear/proportional temperature control or a similar method rather than an ON/OFF method.

INSTALLATION

Recommended mounting method: Clamp with uniform pressure to a flat surface with thermal interface material. For additional information, please refer to our TEC Installation Guide.

II-VI Marlow – Dallas, TX USA
214-340-4900
877-627-5691
marlow.sales@ii-vi.com

Marlow Industries Europe
GmbH - Germany
+49 (0) 6150 5439 - 403
info@marlow-europe.eu

II-VI Japan Inc.
81 43 297 2693 (tel)
center@ii-vi.co.jp
www.ii-vi.co.jp



II-VI Singapore Pte., Ltd.
(65) 6481 8215 (tel)
info@ii-vi.com.sg

Marlow Industries China, II-VI
Technologies Beijing
86-10-643 98226
info@iivibj.com




TYPICAL PERFORMANCE CURVES

ENVIRONMENT: ONE ATMOSPHERE DRY NITROGEN



For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, contact one of our Applications Engineers at 877-627-5691.

MECHANICAL CHARACTERISTICS



For customer support or general questions please contact a local office or visit our website at www.marlow.com.